

VST Series: Two Stage, Variable Speed Control Rotary Screw Air Compressors



225–260 kW, VST 225/260

Efficiency

Gardner Denver designed and built this product using the latest technology for optimizing the energy efficiency of the entire package. Computational Fluid Dynamics (CFD) was used to minimize pressure drop and optimize volumetric efficiency. Finite Element Analysis (FEA) allowed critical components to be reviewed for strength and durability. Thermography allowed us to design the most effective cooling system for the package. **The result: Least operational power cost resulting in bottom line profit to your company.**

Flexibility

The combination of the new AirSmart™ controller with Variable Frequency Drives provides you with a compressor that will meet all of your variable pressure and flow requirements with no interruptions. The controller allows the operator to change the target pressure of the unit with the touch of a button. The variable speed control matches the output of the compressor package to the exact requirements of your system demand. **The result: Maximum flexibility with minimum energy costs resulting in bottom line profit to your company.**

Serviceability

Gardner Denver designed this product with maximum “up time” in mind. The layout of the enclosure, the electronics and the mechanical components minimizes the time required for “normal” maintenance items as well as major mechanical components.


The result: Minimum labor required for maintenance resulting in bottom line profit to your company.

GD
GARDNER DENVER™

Experience Proven Results™

Technical Data VST Series

VST 225/260
(300/350 HP) 60 Hz



Gardner Denver Model	Rated Pressure		Capacity at Rated Pressure*		Motor Power		Compressor Net Weight (Cooling Module Wt)		Air Outlet Size	Noise Level**
	psig	bar	acfm	m ³ /min	hp	kW	lbs	kg		
VST 225	100	6.9	1728	48.9	300	225	14,572 (4,108)	6,610 (1,863)	4" – 150# ANSI Flange	80
	125	8.6	1607	45.5						
	150	10.3	1474	41.7						
	175	12.1	1369	38.8						
VST 260	100	6.9	2032	57.5	350	260	14,572 (4,108)	6,610 (1,863)	4" – 150# ANSI Flange	80
	125	8.6	1885	53.3						
	150	10.3	1761	49.9						
	175	12.1	1627	46.1						

* Capacity measured in accordance with CAGI/PNEUROP acceptance test code PN2CPTC2.

** Noise level measured in accordance with ISO 2151.

Standard Equipment

- Direct Drive, Non-Geared energy efficient airend design
- Optimized drive/motor/airend combinations for maximum efficiency of both compression stages
- Innovative AirSmart controller monitors and controls the unit to obtain optimum efficiency
- Multi-language capability in controller interface
- IP54 rated control enclosure with filters
- TEFC inverter duty 460 volt motor design, Class F insulation, rated at 45° C ambient operation

- Air/oil separation to < 2 ppm per ISO 8573-2
- Unlimited motor "Starts" due to drive design
- Pressure relief valve
- Centrifugal cooling fan driven by variable speed drive/motor combination
- After-cooler designed for 15° F CTD
- Efficient moisture separator with "Float" drain
- Enclosure designed to minimize noise emissions
- Factory fill of AEON® 9000TH synthetic lubricant
- EMC Filter Standard on VST 260

- AirSmart controller features:
 - Extremely user friendly programming
 - Operation modes: Automatic or Start/Stop operation
 - 4 x 20 character LCD display with LED back lighting
 - Adjustable Maintenance advisories
 - Programmable "Distributor Contact Information" for maintenance
 - Maintenance advisories include part number
 - Easy to navigate to additional screens
 - Indicates capacity level at a glance

Optional Equipment

- Line reactors
- EMC filter optional on VST 225
- Watercooled
- Communications/Sequence Module
- AEON 6000FG-68 High Temp Food Grade Lubricant
- Auto water temperature regulator

Gardner Denver®

www.GardnerDenverProducts.com

Gardner Denver, Inc. 1800 Gardner Expressway, Quincy, IL 62305

www.contactgd.com/compressors

866-440-6241



Please recycle after use.